

Za tehnično podporo ali pomoč pokličite  
**090-6009**



## ProGlove MARK display **Brošura**

Več informacij: <http://www.info-kod.si>

---

Vprašanja? Kontaktirajte naše strokovnjake



090-6009



servis@info-kod.si



<http://www.info-kod.si>

Ponedeljek – Petek od 9:00 do 15:00

## Technical Specification

### ProGlove MARK Display

#### WIRELESS COMMUNICATION

##### BLUETOOTH LOW ENERGY

BLUETOOTH RADIO	Supports Bluetooth Low Energy 4.0, 4.1, 4.2, 5.0
TRANSMISSION RANGE	Free field: 40 m (131 ft)** Indoor: 10-20 m (33-66 ft)** **may decrease in industrial environments (e.g. due to walls, metal shelving, machines)

##### BARCODE DECODING CAPABILITIES

1D	Auto decodes all standard 1D codes including GS1 DataBar linear codes et al.
2D	PDF417, MicroPDF417, Data matrix, QR Code, Micro QR Code, Aztec, MaxiCode, et al.
POSTAL	US PostNet, US Planet, UK Postal, Australia Postal, Japan Postal, Dutch Postal (KIX) et al.

##### DISPLAY

DISPLAY	E-PAPER DISPLAY
SIZE	1.54 inch
RESOLUTION	200 x 200 pixel resolution, 188 Dpi

##### ELECTRICAL PROPERTIES

BATTERY	670 mAh, Lithium polymer (rechargeable)
CHARGING TIME	2 hours with ProGlove Charging Station
OPERATING TIME / SCANS	approx. 6000 scans depending on the application and environmental conditions

##### MECHANICAL PROPERTIES

DIMENSIONS	50 x 45 x 18 mm (1.47 x 1.77 x 0.7 in)
WEIGHT	48 g (1.7 oz)

##### ENVIRONMENTAL CONDITIONS

DROP RESISTANCE	50 drops from 2 m (6.5 ft) onto concrete
TUMBLES	500 tumbles from 1 m
PROTECTION AGAINST DUST AND WATER	IP 54
TEMPERATURE	Operating Temperature: 0°C - 45°C (32°F - 113°F) Charging Temperature: 5°C - 40°C (41°F - 104°F) Storage Temperature: -20°C - 60°C (-4°F - 140°F)
HUMIDITY	5% - 95% non condensing
ELECTROSTATIC DISCHARGE (ESD)	±19kVdc air discharge ±17kVdc contact discharge

##### INTERFACES

ANDROID	Insight Mobile (App/SDK)
IOS	ProGlove iOS SDK
USB	ProGlove Gateway

##### SCANNER PROPERTIES

READING FIELD OF VIEW	horizontal: 31°, vertical 23°
SKREW, PITCH & ROLL	Skew tolerance: ±60° Pitch tolerance: ±60° Roll tolerance: 360°
AMBIENT LIGHT	0 - 96,900 lux
AIMER	650 nm, 1 mW

##### UTILITIES & ACCESSORIES

CONFIGURATION & DEVICE MANAGEMENT	<a href="https://insight.proglove.com">https://insight.proglove.com</a>
DEVELOPER DOCUMENTATION	<a href="https://developers.proglove.com">https://developers.proglove.com</a>
ANDROID INTEGRATION	Insight Mobile: Provides a full featured integration for Android enterprise applications.
GATEWAY INTEGRATION	ProGlove Gateway: Hardware connector to enable the full capabilities of the ProGlove Ecosystem via USB-Interface.
TRIGGER	Scanner can be triggered only with ProGlove wearables (REEL, Index-Trigger et al.)

##### SCAN RANGES

Minimum distance determined by symbol length, scan-angle and environmental conditions

##### MID RANGE

5 mil (0.127 mm) code 128	7.4 in./18.8 cm to 16.0 in./40.6 cm
5 mil (0.127 mm) PDF417	8.1 in./20.6 cm to 13.1 in./33.3 cm
10 mil (0.254 mm) DataMatrix Example: A 10 mil DataMatrix symbol, which can carry 25 alphanumeric characters, has a size of 4.57 mm * 4.57 mm	7.0 in./17.8 cm to 17.0 in./43.2 cm
100% UPCA	2.3 in./5.8 cm to 38.0 in./96.5 cm
20 mil (0.508 mm) code 39	2.1 in./5.3 cm to 54.0 in./137.2 cm
100 mil (2.54 mm) code 39	11.0 in./ 27.9 cm to 172.0 in./ 436.9 cm

##### WARRANTY & SLA

WARRANTY	12 months factory warranty
PROGLOVE CARE	36 and 60 months maintenance contracts available. For more information please contact your ProGlove representative or visit <a href="https://proglove.com">https://proglove.com</a>

##### SAFETY & REGULATORY

RADIO AND ELECTROMAGNETIC COMPATIBILITY	EU: 2014/53/EU Radio Equipment Directive (RED) FCC ID: 2A0JL-MARK-2 IC: 23450-MARK2
ELECTRICAL SAFETY	EU: acc. to 2014/53/EU Radio Equipment Directive (RED) EN 62368-1:2014 / A11: 2017  INTERNATIONAL: IEC 62368-1:2014  US/CD: UL 62368-1, 2 <sup>nd</sup> Ed, 2014-12-01 and CAN/CSA C22.2 No. 62368-1-14
LASER CLASSIFICATION	According to EN 60825-1: 2014 and IEC 60825-1 (Ed. 3.0) Laser class 2 device. Caution Laser Radiation - Do not stare into beam.
ENVIRONMENTAL	RoHS Directive 2011/65/EU; Amendment 2015/863, REACH SVHC 1907/2006

##### COUNTRY CERTIFICATION

Regulatory markings are affixed to the device, indicating that the radio modules are approved for use in the following regions: European Economic Area\*, Canada, United States of America, United Mexican States

Detailed information on the regulatory markings can be found in the Declaration of Conformity (DoC) at [www.proglove.com](http://www.proglove.com)

\*CE is valid in the European Economic Area and additional countries: Austria, Belgium, Bulgaria, Croatia, Republic of Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, United Kingdom, Iceland, Liechtenstein, Switzerland and Norway.